

**Hochleistungsspeicher**  
**High-performance storage**  
**Stockage haute performance**  
**Storage ad alte prestazioni**  
**HR/E 120 – 150**



**Emailliert**  
 Enamelled | Émaillés | Smaltato

Leistungstabellen | performance tables | tableaux de performance | tabelle delle prestazioni

HR/E		120				150			
<b>Glattrohrwärmetauscher</b> Heating coil Échangeurs de chaleur Serpentino	<b>m<sup>2</sup></b>	0.6				1.4			
<b>Vorlauf</b> Supply Alimentation Mandata	<b>°C</b> <b>ΔT =</b> <b>10°C</b>	50	60	70	80	50	60	70	80
<b>Spitzenleistung</b> Top performance Sortie crête Potenza di picco	<b>45°C</b> l/10 min.	94	100	110	115	120	140	160	175
	<b>45°C</b> l/h	160	210	250	300	280	390	500	610
<b>Dauerleistung</b> Continuous output Régime permanent Potenza continua	<b>45°C</b> l/h	84	130	175	220	190	300	410	520
<b>Leistung</b> Performance Performance Prestazione	<b>kW</b> <b>(10°C –</b> <b>45°C)</b>	3.4	5.3	7.2	9.1	7.8	12.3	16.8	21.2
<b>Spitzenleistung</b> Top performance Sortie crête Potenza di picco	<b>60°C</b> l/10 min.	-	-	105	110	-	-	130	140
	<b>60°C</b> l/h	-	-	190	220	-	-	320	400
<b>Dauerleistung</b> Continuous output Régime permanent Potenza continua	<b>60°C</b> l/h	-	-	100	130	-	-	230	310
<b>Leistung</b> Performance Performance Prestazione	<b>kW</b> <b>(10°C –</b> <b>60°C)</b>	-	-	5.8	7.7	-	-	13.4	17.9
<b>Heizwasser Primär</b> Heating water primary Eau de chauffage primaire Riscaldamento acqua primaria	<b>m<sup>3</sup> / h</b>	-	-	-	1.0	-	-	-	2.0
<b>Druckverlust</b> Pressure loss Perte de charge Perdita di pressione	<b>mbar</b>	-	-	-	20	-	-	-	60

